

RS320 Series Stick Reader ISO Compatible

With Integral Battery Pack and LCD Readout

Model RS320-3-60/RS320-3-45



General Description

The Allflex Model RS320 Series Stick Reader is an extremely rugged hand-held passive transponder reading device that provides cable-free operation through its internal rechargeable battery pack. Like its predecessor Model RS250 Series, the RS320 Series is compatible with the technical specifications of ISO Standards 11784 and 11785, including both FDX-B and HDX technologies. The RS320 Series Stick Reader provides the basic RFID reader functions of reading, storing, displaying, and transmitting via RS232 serial data the identification code contained within passive transponder for real time and batch mode data logging. The user interface consists of (1) a large thumb-actuated Read button, (2) a Red "Exciter Active" visual indicator, (3) an audible beeper and Green "Good Read" visual indicator, and a two line by 16 character LCD readout that displays the tag number information, tag type, and tag counter. Power is provided to the RS320 Series through its internal 9.6 VDC rechargeable battery pack, which provides sufficient operating time to fill the Stick Reader's internal 3,000+ tag number memory. Serial data and battery charging are connected to the Stick Reader through a detachable one meter long coiled cable or a three meter long straight cable, which are terminated with a DB9(f) data connector containing an integral coaxial power jack. The Stick Reader is provided with a Windows® based PC utility *Configurator*®, which provides users an easy means of customizing the Stick Reader's serial data format and operating modes. Can be upgraded for Bluetooth® capabilities with optional Bluetooth® module (RS-Module-BT).



Construction

The Allflex Series Stick Reader is assembled in a rugged fiberglass tube enclosure that has been designed to be easy to hold and operate with either hand, and is convenient to position in the vicinity of the transponder being scanned. The scanning antenna coil is internally mounted in the forward end of the tube and is oriented for optimal read distance with ear tags when the axis of the transponder is coaxial to the axis of the enclosure tube. This antenna produces a read zone that extends 360° around the end of the tube in axial and radial planes, allowing transponders to be read in any relative orientation. The Allflex Series Stick Reader is available in 45cm and 60cm lengths, and weighs approximately 0.68 kg (24 ounces), including the battery pack.

Performance Capabilities

The Allflex Series Stick Reader is capable of reading the Allflex 30mm HDX/HP ear tag transponder at a minimum distance of 35cm (13.77") (optimum orientation). FDX-B eartag transponders can be read at a minimum distance of 22cm (8.66").

Ordering Information

SKU	Description
Allflex Model RS320-3-60	60cm Length
Allflex Model RS320-3-45	45cm Length

Accessories

AK320	Battery Pack Fast Charger
PW320	Replacement Battery Pack 9.6VDC
RS-Module-BT	Bluetooth® Module for RS320 Series Stick Reader

Allflex USA, Inc.

P.O. Box 612266 * Dallas/Fort Worth Airport, TX 75261-2266
800-989-TAGS (8247) * Customer Toll Free FAX 877-456-3969

Allflex Canada

4135 Berard * St. Hyacinthe, Quebec J2S 8Z8
866-505-TAGS (8247) * FAX 450-261-8028

www.allflexusa.com

RS320 Series Stick Reader ISO Compatible

With Integral Battery Pack and LCD Readout

Model RS320-3-60/RS320-3-45

SPECIFICATIONS

GENERAL

Form Factor:	Portable Handheld Fiberglass Tube Enclosure w/Rubber Handle Grip
User Interface:	Single "Press to Read" Activation Button Red LED "Exciter Active" Visual Indicator Audible Beeper and Green LED "Good Read" Visual Indicator 2 x 16 LCD Readout for tag number, tag type, and tag counter information RS232 Serial Data Port Software upgradeable via RS232 serial port
RS232 Serial Port:	1200 BPS to 57.6 KBPS (9600N81 default setting)
Serial Data ID Code Format	Decimal or Hexadecimal Mfr/Country Code + National ID Code
Memory:	Stores 3,000+ transponder codes in non-volatile memory for download
User Options:	Non-volatile mode control options selectable via RS232 serial port interface
Power/Data Interface:	Detachable 1 meter coiled cable (extends to 3 meters) or 3 meter straight cable w/DB9(f) connector & 2.5mm x 5.5mm coaxial power jack
Battery Power:	Internal 9.6 VDC Rechargeable NiMH Battery Pack
Agency Certifications: (PENDING)	Electromagnetic Compatibility - FCC Part 15 Class A, Industry Canada RSS-210, and CISPR 22 (EN55022), and EN50082-1 Product Safety - UL1950, IEC950 (CE Marked) ISPRA Certification

PHYSICAL/ENVIRONMENTAL

Dimensions:	45cm L (RS320-45-3) or 60cm L (RS320-60-3) x 32mm diameter
Weight:	0.62 kg. (22 ounces)
Material:	UL94V0 Fiberglass and ABS UL94 HB Plastic
Color:	Yellow / Black
Operating Temperature	-10°C to +55°C (IEC68.2.1/.2)
Storage Temperature	-40°C to +85°C (IEC68.2.1/.2)
Humidity:	0 to 95% (IEC68.2.56)
Altitude:	-100 to +3,000 meters
Mechanical Shock:	Per IEC 68-2-27 (15g/11ms sawtooth) & 1 meter free-fall drop onto concrete)
Vibration:	Per IEC 68-2-6 (10-55 Hz sinusoidal/0.75mm displ./1 oct/min./10 cycles)

RELIABILITY

MTBF:	50,000 hours
MTTR:	0.5 hours (not field serviceable)
Expected Life:	5 years, minimum

Read Distance: (@ 9.6 VDC)	35cm (13.77") (minimum - Allflex 30mm HDX/HP eartag) 22cm (8.66") (minimum - Allflex 31mm FDX-B eartag)
Reading Orientation:	0° to 45° with less than 10% range decrease
Read Zone:	360° in radial and axial planes with respect to end of reader enclosure
Interrogation Rate:	~ 9 times/second
Read Error Rate:	Less than 1 in 10 ⁶
Exciter Signal Radiated Field Strength:	84 dBuV/m @ 10 meters with 9.6 VDC power input

